

## 1. IDENTIFICATION OF PRODUCT AND COMPANY

**Product Name** : 70000-00801 Ink, black

**Use of the substance/preparation:** Ink for industrial ink jet printers (CIJ-printers)

**Supplier** : Paul Leibinger Inc  
2702 Buell Drive, Suite B  
East Troy, WI 53120, USA  
Phone: +01-262-642-4030  
[www.leibinger-group.com](http://www.leibinger-group.com)

**Emergency phone (24h service)** : USA: ChemTel Inc: +1-800-255-3924  
Outside USA: ChemTel Inc: +1-813-248-0585  
Brazil: ChemTel Inc: +1-800-591-5042  
Mexico: ChemTel Inc: +1-800-099-0731

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225  
Eye Irrit. 2, H319  
STOT SE 3, H336  
Aquatic Chronic 3, H412

### 2.2 Label elements

**Hazard pictograms:**



**Signal word** : Danger

#### Hazard statements :

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Hazardous ingredients:** butanone

### 2.3 Other hazards

**Other hazards which do not result in classification:** None known

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance / mixture: Mixture

Chemical name	CAS No	EC No	[% weight]	Regulation (EC) No. 1272/2008 [CLP]	Typ
butanone	78-93-3	201-159-0	50 < 80	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
isopropyl acetate	108-21-4	203-561-1	5<10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
propan-2-ol	67-63-0	200-661-7	2.5<5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
Monoazo chrome complex dye	59307-49-2	261-691-4	1<2.5	Aquatic Chronic 2, H411	[1]
Solvent Brown 44	57206-81-2	260-616-2	1<2.5	Aquatic Chronic 2, H411	[1]
Acid Blue 317	64611-73-0	264-966-7	1<2.5	Aquatic Chronic 2, H411	[1]
Chromate (III) complex dye	57206-83-4	260-617-8	1<2.5	Aquatic Chronic 2, H411	[1]
				<b>See Section 16 for the full text of the H statements declared above.</b>	

See section 16 for the full text of the R-phrases declared above

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been

**assigned a workplace exposure limit and hence require reporting in this section.**

**[1] Substance classified with a health or environmental hazard**

**[2] Substance with a workplace exposure limit**

**Occupational exposure limits, if available, are listed in section 8.**

### 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

**General:** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.

**Eye contact:** Check for and remove any contact lenses. Immediately flush eyes with room temperature water for at least 15 minutes, keeping eyelids open. In case of accidental eye contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of the eyes.

**Inhalation:** Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel..

**Skin contact:** Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use solvents or thinners. In case of accidental skin contact, avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of skin

**Ingestion:** If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

**Protection of first-aiders :** No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to medical doctor:** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments:** No specific treatment.

### 5. FIRE-FIGHTING MEASURES

#### 5.1 Extinguishing media

**Suitable extinguishing media:** Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media:** Do not use water jet

#### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture:** Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous thermal decomposition products:** Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen

#### 5.3 Advice for firefighters

**Special protective actions for fire-fighters:** Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters:** Appropriate breathing apparatus may be required.

### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8

**For emergency responders :** If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also Section 8 for additional information on hygiene measures.

**6.2 Environmental precautions:** Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and materials for containment and cleaning up:** Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling:

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

### 7.2 Conditions for safe storage, including any incompatibilities:

Store between the following temperatures: 5 - 30 °C

Store in accordance with local regulations.

### Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking.

Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

### 7.3 Specific end use(s)

**Recommendations :** Not available.

**Industrial sector specific solutions:** Not available.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Occupational exposure limits:

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
butanone	EU OEL (Europe, 12/2009). Notes: list of indicative occupational exposure limit values. Skin STEL: 900 mg/m <sup>3</sup> 15 minute(s). STEL: 300 ppm 15 minute(s). TWA: 600 mg/m <sup>3</sup> 8 hour(s). TWA: 200 ppm 8 hour(s).

**Recommended monitoring procedures:**

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**8.2 Exposure controls****Appropriate engineering controls:**

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

**Individual protection measures:****Hygiene measures :**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection**

Use safety eyewear designed to protect against splash of liquids.

**Skin protection / Hand protection:**

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection:**

Personnel should wear antistatic clothing made of natural fibers or of high- temperature-resistant synthetic fibers.

**Respiratory protection:**

If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators

**Environmental exposure controls:**

Do not allow to enter drains or watercourses

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid.
<b>Color:</b>	black
<b>Odor:</b>	Characteristic
<b>Flash point:</b>	<6°C
<b>Lower explosion limit:</b>	Lower: 1.8% Upper: 11,5%
<b>VOC :</b>	86%
<b>Boiling point :</b>	Lowest known value: 78°C (173°F)
<b>Upper/lower flammability or explosive limits:</b>	Lower: 1.8% Upper: 11,5%
<b>Vapor pressure :</b>	10.5 kPa (78.75 mm Hg)
<b>Vapor density :</b>	2.41 [Air = 1]
<b>Relative density :</b>	Not tested
<b>Solubility(ies) :</b>	Not tested
<b>Auto-ignition temperature:</b>	404°C (760°F)
<b>Decomposition temperature:</b>	Not applicable
<b>Viscosity:</b>	Not tested
<b>Explosive properties:</b>	Not applicable.
<b>Oxidizing properties:</b>	Not applicable.
<b>VOC content:</b>	86% by weight
<b>VOC content:</b>	-701g/l

### 9.2 Other information

No additional information.

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity :** No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability :** Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions:** under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid:** When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials:** Keep away from: free radical initiators, peroxides, strong alkalis, reactive metals.

**10.6 Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced

## 11. TOXICOLOGICAL INFORMATION

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### 11.1 Information on toxicological effects

#### Acutetoxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butanone	LD50 Dermal	Rabbit	6480mg/kg	-
	LD50 Oral	Rat	2737mg/kg	-
Isopropyl acetate-	LD50 Oral	Rat	6750mg/kg	-
Propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-

#### Irritation/Corrosion

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]]

#### Sensitization

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### Mutagenicity

Not applicable.

#### Carcinogenicity

Not applicable.

#### Reproductive toxicity:

Not determined - Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

#### Teratogenicity:

Not applicable

## 12. ECOLOGICAL INFORMATION

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

### 12.1 Toxicity

butanone	Acute EC50 5091000 to 6440000 µg/l Fresh water	Daphnia - Daphnia magna - LARVAE - <24 hours	48 hours
	Acute LC50 5600000 µg/l Fresh water	Fish - Gambusia affinis – Adult	96 hours
	Chronic NOEC <70000 µg/l Fresh water	Daphnia - Daphnia magna - <=24 hours	48 hours
	Chronic NOEC 400 ppm Marine water	Fish - Cyprinodon variegatus - Juvenile (Fledgling, Hatchling, Weanling) - 8 to 15 mm	96 hours
Isopropyl acetate	Acute LC50 1100000 µg/l Marine water	Crustaceans - Artemia salina - Nauplii	48 hours
propan-2-ol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200000 µg/l Fresh water	Fish - Rasbora heteromorpha - 1 to 3 cm	96 hours

**12.2 Persistence and degradability:** Not available.

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
butanone	0.3	-	low
Isopropyl acetate	1.3	-	low
propan-2-ol	0.05	-	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>) :** Not available.

**Mobility:** Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects:** No known significant effects or critical hazards.



## 13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information, contact your local waste authority.

### 13.1 Waste treatment methods

#### Product

##### **Methods of disposal**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

#### Packaging

##### **Methods of disposal**

The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**European Waste Catalogue (EWC):** 08 03 12 waste ink containing dangerous substances

**Special precautions:** This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## 14. TRANSPORT INFORMATION

	<u>ADR/RID</u>	<u>IMDG</u>	<u>IATA-DGR</u>
14.1. UN number	1210	1210	1210
14.2. UN proper shipping name	PRINTING INK (butanone)	PRINTING INK (butanone)	Printing ink (butanone)
14.3. Transport hazard class(es)	3	3	3
14.4. Packing group	II	II	II
14.5. Environmental hazards	Yes	Yes	Yes

**Additional Information:**      **Special provisions** 640 (C)  
   **Tunnel code** (D/E)

### 14.6. Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available.

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

#### Annex XIV - List of substances subject to authorization

#### Substances of very high concern:

None of the components are listed

#### **Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles:**

Not applicable

#### Other EU regulations

**Industrial use:** The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work

### 15.2 Chemical Safety Assessment:

This product contains substances for which Chemical Safety Assessments are still to be received

## 16. OTHER INFORMATION

CEPE Classification : 1

#### **Abbreviations and acronyms :**

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

#### **Full text of abbreviated H statements:**

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 may cause drowsiness and dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### **Full text of classifications [CLP/GHS]:**

Aquatic Chronic 2, H411 AQUATIC HAZARD (LONG-TERM) - Category 2

Aquatic Chronic 3, H412 AQUATIC HAZARD (LONG-TERM) - Category 3

Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Liq. 2, H225 FLAMMABLE LIQUIDS - Category 2

STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3

#### Notice to reader

*The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.*